

PF Series Spherical Polypropylene Floats

BOB® polypropylene floats are made in the USA and are lightweight, corrosion-resistant and suitable for use in a broad range of destructive fluids. They are designed for open tank service only in applications where temperatures do not exceed 175°F. Connection type varies by model between a female thread spud connection, slotted connection and universal thread connections. The PF5, PF6 and PF8 models are black UV resistant.



Construction: Plastic

RBS Part Number	Description	Float Diameter	Buoyancy (LBS)	Female Spud Connection	Weight (LBS)
4019113	PF5	5"	1/4-20	2.17	0.18
	PF6	6"	1/4-20	3.81	0.28
	PF6-7	6"	5/16-18	3.81	0.28
4019115	PF8	8"	3/8 NPT	9.87	1.00
	PF8-1	8"	1/4-20	9.87	1.00
	PF8-2	8"	3/8-16	9.87	1.00
	PF8-7	8"	5/16-18	9.87	1.00

Description	Fits Rod Diameter	Hole Size	Buoyancy (LBS)	Female Spud Connection	Weight (LBS)
PF8-SR250	1/4"	0.300"	9.00	3/8 NPT	1.00
PF8-SR375	3/8"	0.406"	9.00	3/8 NPT	1.00
PF8-SR500	1/2"	0.550"	9.00	3/8 NPT	1.00
PF8-SR625	5/8"	0.656"	9.00	No Spud	1.00
PF8-SR750	3/4"	0.812"	9.00	No Spud	1.00
PF8-SR875	7/8"	0.921"	9.00	No Spud	1.00

R1340 Series Stainless Steel Floats

BOB® stainless steel floats are made in the USA from two halves of AISI grade 316 stainless steel welded together. This material provides an increased resistance to corrosion and chemicals. Stainless steel floats are ideal for high pressure, high temperature applications where corrosion or sanitation is a concern. Each model has a female thread spud connection.



Construction: Stainless Steel

Description	Float Diameter	Buoyancy (LBS)	Female Spud Connection	Weight (LBS)
R1340-3	3"	0.21	1/4-20 SAE	0.19
R1340-4	4"	0.65	1/4-20 SAE	0.44
R1340-5	5"	1.55	1/4-20 SAE	0.81
R1340-6	6"	2.15	1/4-20 SAE	1.19
R1340-7	7"	3.09	3/8 NPT	1.75
R1340-8	8"	6.44	3/8 NPT	1.81
R1340-10	10"	11.63	1/2 NPT	7.19
R1340-12	12"	22.25	3/4 NPT	9.75

The data provided above is for information purposes only and no warranty of accuracy or reliability is given. Ross Brown Sales Pty Limited reserves the right to change or modify this data without prior notice.