

## ASME Safety Valves


### Model ST

- Standard safety valve for small air compressor systems and related applications.
- Compact size.
- High flow capacity.
- Resilient rubber pad (silicone or fluorocarbon) insures valve is bubble-tight to within 10% of set pressure.
- All brass construction with zinc-plated piano wire spring.
- Stamped with "UV" and "NB" symbols.
- Set pressure tolerance  $\pm 3\%$  of set pressure.
- 120°C max. temperature.



Model	Connection	Set Pressure	Pad Material	Dimensions (mm)		Weight (gms)	Part Number
				Height	Hex		
ST12	1/8" NPT	25-350 PSI	Optional	51	17.5	60	On Request
ST25	1/4" BSPT/NPT	25-350 PSI	Optional	51	17.5	60	On Request
ST38	3/8" NPT	25-350 PSI	Optional	51	17.5	60	On Request
<i>Stocked Items</i>							
ST25	1/4" BSPT	172 kPa	Silicone	51	17.5	60	4010650
ST25	1/4" BSPT	241 kPa	Silicone	51	17.5	60	4010675
ST25	1/4" BSPT	262 kPa	Silicone	51	17.5	60	4012676
ST25	1/4" BSPT	290 kPa	Silicone	51	17.5	60	4012678
ST25	1/4" BSPT	345 kPa	Silicone	51	17.5	60	4010677
ST25	1/4" BSPT	414 kPa	Silicone	51	17.5	60	4010700
ST25	1/4" BSPT	552 kPa	Silicone	51	17.5	60	4010710
ST25	1/4" BSPT	758 kPa	Silicone	51	17.5	60	4010800
ST25	1/4" BSPT	862 kPa	Silicone	51	17.5	60	4010900
ST25	1/4" NPT	862 kPa	Silicone	51	17.5	60	4010950
ST25	1/4" BSPT	965 kPa	Silicone	51	17.5	60	4011000
ST25	1/4" BSPT	1035 kPa	Silicone	51	17.5	60	4012000
ST25	1/4" BSPT	1090 kPa	Silicone	51	17.5	60	4012200C
ST25	1/4" BSPT	1379 kPa	Silicone	51	17.5	60	4012290
Test Certificate (Optional)							4014995

Flow Chart




### Model SA

- Designed for high temperature applications such as intercoolers and after-coolers, where a compact size is required.
- All brass construction, stainless steel spring and stainless steel ball seating on brass seat.
- Stamped with "UV" and "NB" symbols.
- Set pressure tolerance  $\pm 3\%$  of set pressure.
- 200°C max. temperature.



Model	Connection	Set Pressure	Dimensions (mm)		Weight (gms)	Part Number
			Height	Hex		
SA12	1/8" NPT	50-350 PSI	54	17.5	70	On Request
SA25	1/4" NPT	50-350 PSI	54	17.5	70	On Request
SA38	3/8" NPT	50-350 PSI	54	17.5	70	On Request
Test Certificate (Optional)						4014995

Flow Chart



The data provided above is for information purposes only and no warranty of accuracy or reliability is given.  
Ross Brown Sales Pty Limited reserves the right to change or modify this data without prior notice.