CHEFALARM® THERMOMETER & TIMER

- Interchangeable NTC thermistor probes
- Programmable high/low alarm

The ChefAlarm is a professional cooking thermometer and timer which displays the countdown/up time, current temperature and simultaneously displays both the high/low alarms and max/min temperatures.

The timer is fully programmable, allowing the user to set the countdown/up time to/from 99 hours and 59 minutes. The unit incorporates a large, easy-to-read LCD display with user selectable backlight and a loud audible alarm with adjustable volume to 92dB.

The ChefAlarm also includes a calibration function allowing the user to fine-tune the accuracy of the thermometer (±2.2 °C). The unit is housed in a water-resistant casing and is designed to either sit on a worktop or attach to an appliance using the magnetic pads at the rear of the instrument.

Each unit is supplied in a zip wallet complete with a penetration probe (810-071) and probe holder clip. See opposite page for full probe specification.

Order code	Description	
810-041	ChefAlarm - white	4099790
830-157	Protective zip wallet	





Perfect for protecting and transporting your ETI instrument. Dimensions 50 x 200 x 240 mm







Specification	ChefAlarm
Range	-50 to 300 °C
Resolution	0.1 °C/°F
Accuracy	±1 °C (-20 to 120 °C)
Battery & life	2 x 1.5 volt AAA - 5000 hours
Alarm volume	<92dB
Sensor type	Thermistor
Display	Custom LCD
Dimensions	19 x 70 x 152 mm
Weight	165 grams

## TIMEWASH® TIMER

- Encourages proper hand-washing procedures
- Easily activated by a wave of the hand

This countdown TimeWash timer is designed for use in restaurants, hospitals, schools and in any businesses where hand hygiene is critical. The unit is easy to install and can be mounted on a wall near the sink using Velcro (supplied) or double-sided tape.

The TimeWash timer is easily activated by a wave of the hand that starts the countdown timer. The large clear LCD acts as a visual progress monitor, and when the time is complete the user will hear a loud audible alarm indicating that their hand wash is complete. Incorporating eight pre-set countdown times, 20, 30 and 40 seconds, 1, 2, 3, 4 and 10 minutes, the set time button is discreetly positioned on the rear of the unit.

The TimeWash timer is a great tool to encourage employees to take the time to properly wash their hands by giving them a visual cue.

$\sim$ 1		_ ·	4.4
()rder	code	Descri	ntion

806-201 TimeWash timer



Specification	TimeWash Timer
Range (pre-set)	20, 30 and 40 seconds, 1, 2, 3, 4 and 10 minutes
Resolution	Seconds & Minutes
Accuracy	1% FS
Battery	2 x 1.5 volt AAA
Battery life	3 months
Display	Custom LCD
Dimensions	20 x 91 x 101 mm
Weight	130 grams

