FRIDGE OR FREEZER THERMOMETER

- Internal sensor & external temperature probe
- Programmable high/low audible alarm

This max/min and alarm fridge or freezer thermometer indicates temperature over the range of -24.9 to 69.9 °C with a resolution of 0.1 °C/°F and an accuracy of ±1 °C.

The thermometer features a clear LCD display, max/min memory function to record the highest and lowest temperatures and a high/low programmable audible alarm. The unit incorporates two temperature sensors, a remote water-resistant probe with one metre PVC lead for the appliance temperature and an internal sensor for the room temperature.

The remote probe can be mounted onto the internal wall of the fridge using the suction pad or mounting bracket supplied. The thermometer is housed in a durable ABS case and incorporates a foot stand for shelf mounting.

| Re | emote probe | ERMOMETER MAX/ MIN |
|----|--------------------------------------------------------------|-----------------------------------------------------------------------------------|
| | Specification | Digital fridge or freezer |
| | | |
| | Range | -24.9 to 69.9 °C |
| | Range Resolution | -24.9 to 69.9 °C 0.1 °C/°F |
| | - | |
| | Resolution | 0.1 °C/°F |
| | Resolution Accuracy | 0.1 °C/°F ±1 °C |
| | Resolution Accuracy Battery | 0.1 °C/°F ±1 °C 3 volt CR2032 lithium coin cell |
| | Resolution Accuracy Battery Battery life | 0.1 °C/°F ±1 °C 3 volt CR2032 lithium coin cell 3000 hours |
| | Resolution Accuracy Battery Battery life Display | 0.1 °C/°F ±1 °C 3 volt CR2032 lithium coin cell 3000 hours Custom LCD |

| Order code | Description |
|------------|---------------------------|
| 810-225 | Digital fridge or freezer |

FRIDGE OR FREEZER THERMOMETER

- Programmable high/low audible alarm
- Records the max/min temperatures

This fridge or freezer thermometer features a clear LCD display, max/min, audible alarm and incorporates two temperature sensors; a remote water-resistant probe with one metre PVC lead for the appliance temperature and an internal sensor for the room temperature.

e mounted onto the internal The wa he suction pad or mounting bra ermometer is housed in a corporates a foot stand for dur she

Optional UKAS Certificate of Calibration An optional two-point UKAS Certificate of Calibration is available. Each certificate indicates deviations from standards at -18 and 0 °C.

| Order code | Description | | | |
|-----------------------------------------------|-------------------------------|---------|--|--|
| 810-210 | Fridge or freezer thermometer | 4099788 | | |
| 891-210 | 810-210 with UKAS certificate | 4099787 | | |
| UKAS certificate applies to remote probe only | | | | |



ABN 28 000 690 362 TEL: (02) 8855 1700 FAX: (02) 9899 4233 EMAIL: sales@rossbrownsales.com.au WEBSITE: www.rossbrownsales.com.au

Accuracy

Display Dimensions

Weight

±1°C Battery & life 1.5 volt AAA - 5000 hours Custom LCD

15 x 52 x 73 mm

55 grams



| e remote probe can be Il of the fridge using th acket supplied. The the rable ABS case and inc elf mounting. |
|--------------------------------------------------------------------------------------------------------------------------|
| Optional UKAS Certif |

| | ROSS |
|--|---------------|
| | BROW SALES |