








# HEAVY-DUTY TYPE K OR T THERMOCOUPLE PROBES

			Order code
<p><b>T SHAPED OVEN PROBE</b></p>  <p><b>A HIGH ACCURACY</b> <b>A HIGH ACCURACY</b></p> <p>Ø3.3 x 130 mm</p>	<p>This strong oven penetration probe incorporates a stainless steel T-shaped handle, and a two metre PTFE high temperature lead. Ideal for continuous monitoring applications or where a nylon or polypropylene handle cannot be used.</p> <ul style="list-style-type: none"> <li>• Response time less than 2 seconds</li> <li>• Probe temperature range -75 to 250 °C</li> </ul>	133-174	
<p><b>PENETRATION PROBE</b></p>  <p><b>A HIGH ACCURACY</b> <b>A HIGH ACCURACY</b></p> <p>Ø4 x 100 mm</p>	<p>This robust, stainless steel penetration probe incorporates a T-shaped polypropylene handle and is ideal for a variety of heavy-duty applications including food processing and other similar industries.</p> <ul style="list-style-type: none"> <li>• Response time less than 3 seconds</li> <li>• Probe temperature range -75 to 250 °C</li> </ul>	133-124	
<p><b>REDUCED TIP PROBE</b></p>  <p><b>A HIGH ACCURACY</b> <b>A HIGH ACCURACY</b></p> <p>Ø6.35 x 100 mm or 300 mm</p>	<p>This robust, stainless steel, reinforced probe incorporates a T-shaped polypropylene handle and a reduced sensing tip (Ø4.5 x 25 mm) for faster response. Ideal for a variety of heavy-duty applications including food processing etc.</p> <ul style="list-style-type: none"> <li>• Response time less than 9 seconds</li> <li>• Probe temperature range -75 to 250 °C</li> </ul>	133-126 (100 mm) 133-120 (300 mm)	
<p><b>REDUCED TIP PROBE</b></p>  <p><b>A HIGH ACCURACY</b> <b>A HIGH ACCURACY</b></p> <p>Ø8 x 500 mm</p>	<p>This extended robust, stainless steel, reinforced probe incorporates a T-shaped polypropylene handle and a reduced sensing tip (Ø6.35 x 25 mm) for faster response. Ideal for a variety of heavy-duty applications including food processing etc.</p> <ul style="list-style-type: none"> <li>• Response time less than 20 seconds</li> <li>• Probe temperature range -75 to 250 °C</li> </ul>	133-130      4098968	
<p><b>REDUCED TIP PROBE</b></p>  <p><b>A HIGH ACCURACY</b> <b>A HIGH ACCURACY</b></p> <p>Ø9.5 x 1000 or 1400 mm</p>	<p>This Ø9.5 mm stainless steel, reinforced probe incorporates a T-shaped polypropylene handle and a reduced sensing tip (Ø6.35 x 25 mm) for faster response. Ideal for applications where a longer probe is required, i.e. grain silos.</p> <ul style="list-style-type: none"> <li>• Response time less than 20 seconds</li> <li>• Probe temperature range -75 to 250 °C</li> </ul>	133-136 (1000 mm) 133-135 (1400 mm)      4098970	
<p><b>REDUCED TIP PROBE</b></p>  <p><b>A HIGH ACCURACY</b> <b>A HIGH ACCURACY</b></p> <p>Ø9.5 x 2000 mm</p>	<p>This extended stainless steel, reinforced probe incorporates a T-shaped polypropylene handle and a reduced sensing tip (Ø6.35 x 25 mm) for faster response. Ideal for applications where a very long probe is required, i.e. grain silos.</p> <ul style="list-style-type: none"> <li>• Response time less than 20 seconds</li> <li>• Probe temperature range -75 to 250 °C</li> </ul>	133-133	
<p><b>CORKSCREW PROBE</b></p>  <p><b>A HIGH ACCURACY</b> <b>A HIGH ACCURACY</b></p> <p>Ø8 x 100 mm</p>	<p>This stainless steel probe incorporates a heavy-duty T-shaped polypropylene handle and a corkscrew design sensing tip. Ideal for industrial and food processing applications. Supplied with a one metre PU detachable lead.</p> <ul style="list-style-type: none"> <li>• Response time less than 9 seconds</li> <li>• Probe temperature range -75 to 250 °C</li> </ul>	133-175	

Please note: for handheld type T thermocouple probes, replace the third digit (3) of the order code with the number 7