







PT100 CLASS A TEMPERATURE PROBES

		Order code
<p>PENETRATION PROBE</p>  <p>Ø3.3 x 130 mm</p>	<p>This stainless steel penetration probe is strong, versatile and ideal for measuring liquids and semi-solids accurately in a variety of applications.</p> <ul style="list-style-type: none"> • Response time less than 6 seconds • Probe temperature range -100 to 200 °C 	160-160 4099104
<p>AIR OR GAS PROBE</p>  <p>Ø3.3 x 130 mm</p>	<p>This stainless steel air or gas probe is ideal for measuring air or gas temperatures accurately in rooms and ducts in HVAC and industrial applications.</p> <ul style="list-style-type: none"> • Response time less than 4 seconds • Probe temperature range -100 to 200 °C 	160-300 4099106
<p>LIQUID PROBE</p>  <p>Ø3.3 x 130 mm</p>	<p>This liquid probe features a rigid, stainless steel stem with a flat tip. The probe is suitable for accurate temperature measurement in a wide variety of laboratory applications.</p> <ul style="list-style-type: none"> • Response time less than 6 seconds • Probe temperature range -100 to 200 °C 	160-220 4099108
<p>AIR OR GAS WIRE PROBE</p>  <p>Ø3.7 x 30 mm with 1000 mm FEP lead</p>	<p>This FEP insulated air or gas wire probe is ideal for measuring air or gas temperatures accurately in a variety of HVAC and industrial applications.</p> <ul style="list-style-type: none"> • Response time less than 4 seconds • Probe temperature range -100 to 200 °C 	160-372 4099110

Please note: the above PT100 Class A probes are suitable for use with the Precision 0.1 °C thermometer

PT100 1/10TH DIN TEMPERATURE PROBES

		Order code
<p>LIQUID PROBE</p>  <p>Ø3.3 x 130 mm</p>	<p>This handheld liquid probe features a rigid, stainless steel stem with a flat tip. Suitable for high accuracy temperature measurement in a wide variety of laboratory applications.</p> <ul style="list-style-type: none"> • Response time less than 8 seconds • Probe temperature range -200 to 200 °C 	160-222
<p>LIQUID PROBE</p>  <p>Ø4.8 x 250 mm with 2000 mm PTFE lead</p>	<p>This liquid probe features a rigid, stainless steel stem with a flat tip. Suitable for high accuracy temperature measurement in a wide variety of laboratory applications.</p> <ul style="list-style-type: none"> • Response time less than 14 seconds • Probe temperature range -200 to 200 °C 	160-446

Please note: accuracy of the above PT100 1/10th DIN probes is ±0.03 °C ±0.1 % of reading between -100 °C to 200 °C otherwise ±0.2 % of reading. The above probes are suitable for use with the Precision Plus 0.01 °C thermometer

All PT100's listed on this page are fitted with a Binder Plug.