- FREE traceable certificate of calibration
- Includes Biomaster Antimicrobial Technology
- Temperature range -50 to 300 °C
- One button, simple & easy-to-use

The Thermamite thermometer offers accuracy, flexibility and ease of use, coupled with the durability and reliability that is required by the food and catering industry in helping to meet today's food hygiene legislation.

The thermometer incorporates an easy-to-read, LCD display with a precise read-out of temperature over the range of -50 to 300 °C with a 1 °C resolution. Low battery and open circuit indication are also displayed. The unit will power-off automatically after ten minutes, maximising battery life.

The instrument is housed in an ergonomic, robust ABS case that includes Biomaster Antimicrobial Technology which reduces bacterial growth. Each thermometer is supplied with a permanently attached, pointed stainless steel food penetration probe ($\emptyset 3.3 \times 100$ mm) and a 500 mm PVC lead.

Protective silicone boot

The Thermamite is water-resistant to IP65 when used in conjunction with this boot. Protects from accidental damage. Various colours are available - see page 13





| Order code | Description | |
|------------|----------------------------------|----------|
| 261-010 | Thermamite - white | |
| 261-020 | Thermamite - yellow | |
| 261-030 | Thermamite - green | |
| 261-040 | Thermamite - red | |
| 261-050 | Thermamite - blue | 4099794A |
| 830-221 | Protective silicone boot - white | |
| 832-050 | S/steel wall bracket & boot | |



The wall bracket stores your Thermamite safely away when not in use. Keyhole slot for hanging (screws not supplied).









| Specification | Thermamite | |
|--|--------------------------------|--|
| Range | -50 to 300 °C | |
| Resolution | 1°C | |
| Accuracy | ±1°C/1% of reading | |
| Battery & life | 3 x 1.5 volt AAA - 10000 hours | |
| Sensor type | K thermocouple | |
| Display | 12 mm LCD | |
| Dimensions | 25 x 56 x 128 mm | |
| Weight | 160 grams | |
| FREE traceable certificate of calibration included | | |

