THERMAPEN[®] CLASSIC THERMOMETERS

- Choice of air, surface or penetration probe
- Lightweight, compact & easy-to-use
- High accuracy ±0.4 °C
- One-handed operation

The Thermapen classic thermometer incorporates a large digital display with a precise read-out over the range of -49.9 to 299.9 °C with a 0.1 °C resolution. The resolution can be switched to 1 °C, if required, via a switch in the battery compartment.

The thermometer will power off automatically after ten minutes, maximising battery life. This feature can be disabled if not required. Both low battery (icon) and open circuit indication are also displayed, when applicable. Each industrial Thermapen is powered by two lithium coin cell batteries with a minimum life expectancy of 1500 hours.

The probe conveniently folds back through 180° into the side of the instrument when not in use. The casing is washable and includes Biomaster Antimicrobial Technology that reduces bacteria growth and the ergonomic rubber seal minimises the risk of the ingress of water, dust or food.

• Choice of probe styles

The Thermapen classic thermometer is available with three styles of probe; surface, air or penetration. The fast response air probe is an invaluable tool in establishing the correct air temperature quickly in HVAC and laboratory applications. The surface probe is particularly useful in determining the temperature of hot plates or pipes etc. **Please note:** the accuracy and speed of response will be dependent on whether the surface is flat and heat transfer compound is used.

OPTIONAL ACCESSORIES:

- Protective PVC wallet with belt strap (830-110)
- Protective silicone boot (830-260)
- Glow-in-the-dark silicone boot with magnets (830-265)
- Stainless steel wall bracket (832-002) screws not supplied

Order code	Description	
231-210	Thermapen Classic - penetration probe	4098789
231-212	Thermapen Classic - surface probe	4098785
231-214	Thermapen Classic - air probe	4098784
830-260	Protective silicone boot	4098889
830-265	Silicone boot - glow in dark	4098888
830-110	Protective wallet	4098795
832-002	Stainless steel wall bracket	4098794
The Thermapen is supplied in a zip pouch (830-001)		

Specification Classic Thermapen -49.9 to 299.9 °C Range Resolution 0.1 °C or 1 °C - user selectable ±0.4 °C (-49.9 to 149.9 °C) or ±1 % Accuracy Battery 2 x 3 volt CR2032 lithium coin cell 1500 hours Battery life Sensor type K thermocouple 14.5 mm LCD Display Dimensions 19 x 47 x 153 mm Weight 97 grams FREE traceable certificate of calibration included







Ø8 x 95 mm

This waterproof ribbon surface probe is ideal for measuring the surface temperature of pipes, bearings, hotplates and other flat surfaces.

PENETRATION PROBE

Ø3.3 x 108 mm



INDUSTRIAL

This strong and versatile probe incorporates a pointed, general purpose tip, ideal for insertion into liquids and semi-solids.



0

Ø3.3 x 95 mm

This fast response air or gas probe is ideal for measuring the air temperature in HVAC applications, laboratories and other temperature sensitive working areas.

