

# SJE AMPMASTER® PUMP FLOATS

**Mechanically-activated, wide-angle 20 amp rated switch designed to control pumps up to 1 1/2 HP at 125 VAC and 3 HP at 250 VAC.**

This mechanically-activated, wide-angle 20 amp rated pump switch provides automatic control of grinder and high head sewage pumps in grinder and lift station applications, as well as septic tank effluent pump (STEP) systems.

The **SJE AmpMaster®** pump switch is not sensitive to rotation or turbulence allowing it to be used in both calm and turbulent applications.

**Available for pump down applications only.**



## SPECIFICATIONS

- Flexible SJOW, water-resistant (CPE) cable
- High impact, corrosion resistant, PVC float housing
- Temperature rating up to 50° C (120° F)
- Maximum water depth of 14 meters (46 feet) or 138 kPa (20 psi)
- Float dimensions: 7.75 cm diameter x 9.04 cm long (3.05 inch x 3.56 inch)
- Adjustable pumping range of 23 to 61 cm (9 to 24 inches)
- Heavy-duty contacts mounted on high conductivity copper substrates



**NOTE:** This switch must be used with pumps that provide integral thermal overload protection. Certain pump applications may require the use of an external capacitor start kit.



## SPECIFICATIONS

SJE AMPMASTER® pump float		
Voltage 50 Hz/60 Hz Single Phase	Maximum Pump Running Current	Maximum Pump Starting Current
125/250 VAC	20 amps	120 amps
Cable:	12 gauge, 2 conductor	

**Pump Down** is normally open contacts for emptying.

## OPTIONS

**Mounting Clamp is standard.**  
**Bagged Packaging is standard.**



### Ordering Information

RBS Stock Code	Description
3709110	AmpMaster, 10mtr, No Plug

  
**SJE RHOMBUS.**

9500199C 11/18  
© 2018 SJE, Inc. All Rights Reserved.  
SJE RHOMBUS is a trademark of SJE, Inc.

*The data provided above is for information purposes only and no warranty of accuracy or reliability is given.  
Ross Brown Sales Pty Limited reserves the right to change or modify this data without prior notice.*