

SJE HITEMPMASTER™ PUMP FLOAT

Mechanically-activated, wide-angle pump switch specifically designed for performance and dependability in high temperature sump applications up to 93°C (200°F).

This mechanically-activated, wide-angle switches provide automatic control of pumps in:

- Water
- Sewage applications

This SJE HiTempMaster™ pump switch is not sensitive to rotation or turbulence allowing it to be used in both calm and turbulent applications.

Available for pump down applications only.



SPECIFICATIONS

- Flexible SJOOW, water-resistant (CPE) cable
- High impact, corrosion resistant, polypropylene float housing
- Temperature rating up to 93° C (200° F)
- Maximum water depth of 10 meters (33 feet) or 90 kPa (13 psi)
- Float dimensions: 8.1 cm diameter x 14.2 cm long (3.18 inch x 5.58 inch)
- Adjustable pumping range of 20 to 91 cm (8 to 36 inches)
- Mechanically-activated, snap action contacts



NOTE: This switch must be used with pumps that provide integral thermal overload protection.

MODEL SPECIFIC SPECIFICATIONS

SJE HITEMP MASTER™ pump float		
Voltage 50 Hz/60 Hz Single Phase	Maximum Pump Running Current	Maximum Pump Starting Current
125/250 VAC	12 amps	78/72 amps
Cable:	16 gauge, 2 conductor	

Pump Down is normally open contacts for emptying.
SEE INTERNATIONAL PRICE BOOK FOR LIST PRICING.

Mounting Clamp is standard.

Piggy-Back Plug - North American standard plug.

Boxed Packaging is standard.

Ordering Information

RBS Stock Code Pump Down	Description
3710000	HiTempMaster, 2-wire, 3mtr, No Plug
3710010	HiTempMaster, 2-wire, 6mtr, No Plug
3710014	HiTempMaster, 2-wire, 10mtr, No Plug



9500200D 07/20
 © 2018 SJE, Inc. All Rights Reserved.
 SJE RHOMBUS is a trademark of SJE, Inc.

*The data provided above is for information purposes only and no warranty of accuracy or reliability is given.
 Ross Brown Sales Pty Limited reserves the right to change or modify this data without prior notice.*